

CarbonXP™ Competitor Product Reference Guide

MFG	PRODUCTS	% VISIBLE LIGHT TRANSMISSION (VLT)	% TOTAL SOLAR ENERGY REJECTION (TSER)	% VISIBLE LIGHT REFLECTANCE (VLR)	% UV REJECTION	THICKNESS (mils)
SunTek	CXP 55	53	48	7	>99	1.5
Formula One	Pinnacle 50	54	43	8	99.5	1.5
Llumar	CTX 50	58	35	8	99	1.5
Solar Gard	Ultra-Performance 60	64	37	8	>99	1.5
SunTek	CXP 45	40	50	7	>99	1.5
Formula One	—	—	—	—	—	—
Llumar	CTX 40	43	47	8	99	1.5
Solar Gard	Ultra-Performance 40	43	40	7	>99	1.5
SunTek	CXP 35	33	53	6	>99	1.5
Formula One	Pinnacle 35	39	50	7	99.5	1.5
Llumar	CTX 30	31	50	8	99	1.5
Solar Gard	Ultra-Performance 30	34	43	6	>99	1.5
SunTek	CXP 18	16	56	6	>99	1.5
Formula One	Pinnacle 15	18	59	6	99.5	1.5
Llumar	CTX 15	17	55	8	99	1.5
Solar Gard	Ultra-Performance 20	20	49	6	>99	1.5
SunTek	CXP 5	6	59	5	>99	1.5
Formula One	Pinnacle 5	5	61	8	99.5	1.5
Llumar	CTX 5	5	60	8	99	1.5
Solar Gard	Ultra-Performance 10	10	51	5	>99	1.5

FormulaOne® and Llumar® are trademarks of Solutia Inc.
 Solar Gard® is a trademark of Bekaert Specialty Films, LLC
 The attached chart is to be used for comparison purposes only.

Competitive information and product specifications obtained from llumar.com,
 vista-films.com, solargard.com, and panoramafilm.com on 4/16/2010.